

## HIGHLY PORTABLE SCREENER

The TS2300 is designed for users who require less capacity than the TS2430 and TS2600 models offer, but are not willing to sacrifice the quality features found on the Tesab TS-Range. These features include a High Energy Screenbox, large hopper, and large engine bay.


The TS2300 can employ the steepest screen angle of any three- way-split screening plant currently available, ensuring best-in-class screening ability in materials like sand and peastone.

Users with smaller floats or in areas with strict transport regulations will benefit from the smaller transport dimensions.

## FEATURES & BENEFITS

- 10 x 4.5 heavy duty high energy 2 bearing screenbox
- 130Hp (97kW) engine
- Integrated hydraulic folding stockpiling conveyors
- Remote control tipping grid
- Fast on-site setup time 10 minutes typically





## PERFORMANCE SPECIFICATION

\* Depending on application

DIMENSI	ON SDEC	`IEIC ATI	ON*
DIMENSI	ON SI E	JII IOAII	

Screenbox Size	Tonnage*	No. of Decks	Hopper Capacity	Weight
3m x 1.4m (10′ x 4.5′)	up to 250 TPH	2 decks	6.00m³ (7.85yd³) est.	19,250kgs (42,439lbs)

TRANSPORT DIMENSIONS				
Width	Length (Track)	Height (2 deck track)		
2.50m (8' – 4")	13.21m (44′ – 4″)	3.20m (10′ – 6″)		

